

SAFETY DATA SHEET

Product Name PYNEboard® Moisture Resistant

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name CARTER HOLT HARVEY WOODPRODUCTS AUSTRALIAN GROUP OF COMPANIES
Address 22 prospect St, Box Hill, Victoria, AUSTRALIA, 3128
Telephone 132 321
Fax 1800 891 881
Emergency 132 321
Email enquiriesaus@chhwoodproducts.com.au
Web Site www.chhwoodproducts.com.au
Synonym(s) PYNEboard® MR • PYNEboard® MR Particleboard • PYNEboard® E1 Moisture Resistant • PYNEboard® E0 Moisture Resistant • PYNEboard® E1 MR • PYNEboard® E0 MR • PYNEboard® MR Edge lipped Panels
Use(s) CABINETS · CONSTRUCTION MATERIAL · DOORS · FURNITURE · LAMINATING · VENEERING
SDS Date 03 September 2012

2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

RISK PHRASES

None allocated

SAFETY PHRASES

None allocated

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number	None Allocated	DG Class	None Allocated
Packing Group	None Allocated	Subsidiary Risk(s)	None Allocated
Hazchem Code	None Allocated		

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
PARAFFIN WAX	CAS: 8002-74-2 EC: 232-315-6	Not Available	<2%
WOOD(S) (SOFTWOOD/HARDWOOD)	Not Available	Not Available	>70%
MELAMINE/UREA/FORMALDEHYDE RESIN	CAS: 25036-13-9 EC: 607-497-9	Not Available	<15%
MOISTURE	Not Available	Not Available	5 - 13%
DYE(S)	Not Available	Not Available	<0.2%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running

Product Name PYNEboard® Moisture Resistant

	water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). Due to product form and application, ingestion is considered unlikely.
Advice to Doctor	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flammability	Combustible. May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition. May also evolve hydrogen cyanide when heated to decomposition.
Fire and Explosion	Dry wood dust in high concentrations-in-air and at the temperatures > 204°C (>40g of dust per m ³ of air) may spontaneously explode. Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
Extinguishing	Dry agent, carbon dioxide, foam or water fog. Prevent contamination of drains or waterways.
Hazchem Code	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Spillage	If spilt, collect and reuse where possible.
-----------------	---------------------------------------------

7. STORAGE AND HANDLING

Storage	Store in a cool, dry area.
Handling	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Formaldehyde	SWA (AUS)	1	1.2	2	2.5
Paraffin wax (fume)	SWA (AUS)	--	2	--	--
Wood dust (certain hardwoods such as beech & oak)	SWA (AUS)	--	1	--	--
Wood dust (soft wood)	SWA (AUS)	--	5	--	10

Biological Limits	No biological limit allocated.
Engineering Controls	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.
PPE	
Eye / Face	Not required under normal conditions of use.
Hands	Wear leather gloves.
Body	Not required under normal conditions of use.
Respiratory	Not required under normal conditions of use.



9. PHYSICAL AND CHEMICAL PROPERTIES

Product Name PYNEboard® Moisture Resistant

Appearance	PRESSED BOARDS
Odour	SLIGHT ODOUR
Flammability	COMBUSTIBLE
Flash point	NOT AVAILABLE
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	INSOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Autoignition temperature	> 200°C
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
% Volatiles	NOT AVAILABLE
Density	500 kg/m ³ to 800 kg/m ³

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended conditions of storage.
Conditions to Avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to Avoid	Incompatible with oxidising agents (eg. nitrates) and acids (eg. hydrochloric acid).
Hazardous Decomposition Products	May evolve toxic gases (carbon/ nitrogen oxides, ammonia, formaldehyde, hydrocarbons) when heated to decomposition.
Hazardous Reactions	Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Low to moderate toxicity. Use safe work practices to avoid eye or skin contact and inhalation. This product is bonded by formaldehyde resin and formaldehyde may be released during machining. Product may also release small quantities (<0.01%) of formaldehyde in gaseous form that may dissipate over time. Adverse health effects associated with over exposure formaldehyde are not anticipated due to the product form and its low concentration. Formaldehyde is a respiratory and skin sensitiser, and is classified as a confirmed human carcinogen (IARC Group 1). Wood dust is also classified as a confirmed human carcinogen (IARC Group 1).
Eye	Due to product form and nature of use, the potential for exposure is reduced. Product may only present a hazard if dust is generated. Contact may result in mechanical irritation.
Inhalation	Exposure considered unlikely. An inhalation hazard is not anticipated unless cut, drilled or sanded with dust generation, which may result in irritation of the nose and throat. If heated, over exposure to fumes may result in irritation of the nose and throat, with nausea and headache. Formaldehyde is classified as a confirmed human carcinogen (IARC Group 1) and respiratory sensitiser.
Skin	Low irritant. Prolonged or repeated exposure to dust may result in mild irritation. May cause sensitisation by skin contact.
Ingestion	Ingestion is considered unlikely due to product form.
Toxicity Data	PARAFFIN WAX (8002-74-2) TDLo (subcutaneous) 120 mg/kg (rat)

12. ECOLOGICAL INFORMATION

Environment	Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.
--------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

13. DISPOSAL CONSIDERATIONS

Waste Disposal	Reuse where possible. Not regulated as a hazardous waste by Australian environmental authorities.
-----------------------	---------------------------------------------------------------------------------------------------

Product Name PYNEboard® Moisture Resistant

Off-cuts and general waste material should be placed in containers and disposed of at approved landfill sites or burnt in an approved furnace or incinerator in accordance with disposal authority guidelines. Do not burn in barbeques, combustion stoves or open fires in the home as irritating gases may be evolved.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	None Allocated	None Allocated	None Allocated
Proper Shipping Name	None Allocated	None Allocated	None Allocated
DG Class/ Division	None Allocated	None Allocated	None Allocated
Subsidiary Risk(s)	None Allocated	None Allocated	None Allocated
Packing Group	None Allocated	None Allocated	None Allocated
Hazchem Code	None Allocated		

15. REGULATORY INFORMATION

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Inventory Listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional Information The dust generated from this product is hazardous according to the criteria of ASCC. Early fire hazard properties when tested to AS/NZS 1530 Part 3: Ignitability index: 14 - 16 Spread of flame index: 7 - 8 Heat evolved index: 6 - 10 Smoke developed index: 3 - 4

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

COMBUSTIBLE - EXPLOSIVE CARBONACEOUS DUST: Carbonaceous/organic dusts have the potential, with dispersion, to present an explosion hazard if an ignition source exists. All equipment used to handle, transfer or store this product **MUST BE** cleaned thoroughly prior to cutting, welding, drilling or exposure to any other form of heat or ignition sources. If bulk stored, containers should be ventilated on a routine basis to avoid vapour accumulation (where applicable, eg for flocculants).

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this ChemAlert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Product Name PYNEboard® Moisture Resistant

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
	CNS	Central Nervous System
	EC No.	EC No - European Community Number
	GHS	Globally Harmonized System
	IARC	International Agency for Research on Cancer
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m ³	Milligrams per Cubic Metre
	PEL	Permissible Exposure Limit
	pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
	STOT-RE	Specific target organ toxicity (repeated exposure)
	STOT-SE	Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	TLV	Threshold Limit Value
	TWA/OEL	Time Weighted Average or Occupational Exposure Limit

Revision History

Revision	Description
1.1	Standard SDS Review
1.0	Initial SDS creation

Report Status

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared By

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au

Revision: 1.1
SDS Date: 03 September 2012

End of SDS